

# RO-MAIN

› Lead the herd



## MOTORIZED BOAR CART



OPTIMAL HEAT DETECTION  
AND STIMULATION

### About the Product

**Contact-O-Max** is a remote-controlled, articulated boar cart designed to optimize sow fertility by ensuring sustained and precise snout-to-snout contact with the boar. This rigorous, precise, and reliable heat detection system maximizes stimulation, achieving fertility rates of up to **95%**, while reducing heat returns and late cycles.

Its innovative design enables a single worker to efficiently manage heat detection and stimulation, prioritizing operator safety by eliminating direct contact with the boar. Widely adopted by the global swine industry since 1999, Contact-O-Max has revolutionized sow stimulation without requiring barn modifications and is highly recommended by breeding specialists.

### Key Advantages



#### HIGH MANEUVERABILITY

The articulated boar cart can turn even in the tightest corners. No barn modifications required.



#### QUICK RETURN ON INVESTMENT

Improving your farrowing rates by up to 10% allows you to make your money back in less than 6 months.



#### APPROVED AND TRUSTED

Thousands of satisfied customers around the world since 1999.

## Ro-Main

*Innovation, Performance, Simplicity*

One Person Job



Handy Remote



Snout-to-Snout Contact



## Senior

- Compatible with most barn alleys, designed to navigate 24" x 36" (61 cm x 92 cm) corners.
- Available exclusively in a 23" (59 cm) model.
- Performs best on smooth, even alleyways.
- Optimized for precise forward and backward movement.
- Features a double central articulation for enhanced maneuverability.
- Brake/glider steering and a bottom roller system improve performance, especially in wide alleys.

**WEIGHT:** 483 LBS (219 KG) **LENGTH:** 65" (165 CM)  
**WIDTH:** 23" (59 CM) **HEIGHT:** 61 1/2" (156 CM)



## Junior

- Compatible with any barn alley, capable of navigating 24" x 24" (61 cm x 61 cm) corners.
- Available in 20" (51 cm) and 22" (56 cm) models.
- Designed for uneven alleyways and steep ramps.
- Optimized for smooth forward operation.
- Features a single central articulation combined with a slick multi-hinged front/rear system, ensuring maximum maneuverability around tight corners.

**WEIGHT:** 518 LBS (235 KG) **LENGTH:** 62" (158 CM)  
**WIDTH:** 20" OR 22" (51 OR 56 CM) **HEIGHT:** 62 5/16" (160 CM)



**GET IN TOUCH**

1-877-776-6246  
ro-main.com